

# HYDRAULIC MULTIPOWER PACK

## For Cable Blowing Machines

**The Hydraulic MultiPower Pack is the optimal power source to FastBlown, VariousFlow and PowerfulBlown machines... MultiPower pack fits all!**

### SPECIFICATIONS:

Oil flow 18 l.p.m at 3300 r.p.m.  
Working pressure nominal 100 bar.  
Pressure relief valve Set at 110 bar.  
Pump Gear pump.  
Oil temperature Max. 70° C.  
Hydraulic oil tank capacity Min. 5 litres/max. 7 litres  
Petrol tank capacity 3.1 litres  
Hydraulic system compl. Max. 8 litres  
Filter system (filter element) 25 Micron with by-pass  
Engine Honda GX200QX7 6.5 HP (gross power)  
4-stroke petrol with oil alert system.  
Petrol - normal or unleaded.  
Engine oil 1.1 litres.  
Guaranteed sound power level LWA 100 dB  
Sound pressure level 1 m LPA 88 dB  
Dimensions (LxWxH) 630x530x510 mm  
Weight, without hydraulic oil 54 kg.



### UNIQUE COOLING SYSTEM

The **RING COOLER** is the answer to all demands to a perfect cooling system:

- **No down time**
- **High efficiency**
- **Enough cooling capacity**
- **Lowest Service cost**
- **Easy access**
- **Unaffected by dirt, dust, etc.**

*The cooler is mounted in the front protected from all sides. No parts can enter into the cooler.  
The access is very easy by taking off the sidepanels.  
In front of the cooler is the fan, which is blowing air round the cooler – NOT through the cooler.*

