



Product Description

BCP™ UTP voice category 3 patch panels are 19-inch rack mountable IDC/PCB moulded jack patch panels are available in 50 port density. All panels comply with the EIA/TIA Standard for category 3 and, including ANSI/TIA-568-C.2 Standard of 2009 and ANSI/TIA-568.0-D Standard of 2017.

Every patch panel is made with high quality materials and is tested and certified by 3P.

Features & Benefits

- 3P Certified
- Space-saving high density 1U
- Meets or exceeds the requirement proposed by
 - ANSI/TIA-568-C.2 Standard of 2009
 - ANSI/TIA-568.0-D Standard of 2017
 - TIA/EIA 568 B.2, ISO/IEC 11801 Category 3
- Black electrostatic powder-coated corrosion-resistant steel
- Sturdy aluminium plate around jacks
- Termination accepts 22, 23, 24 and 26 AWG (0.64-0.4) solid wires
- Easy wiring installation fit for 110 punch-down tools
- Phosphor Bronze, 6-50 micro inches gold plated

Applications

- Telecommunications
- LAN

Technical Specifications

Insertion Life	750 cycles minimum
IDC Life	200 times (22-26 AWG solid wire) minimum
Plug/Jack Contact Force	100g minimum using FCC-approved plug
Insulation Resistance	100 Mohms MΩ minimum
Contact Resistance	7 Mohms MΩ maximum
Dielectricity Intensity	AC 1000 Vrms, 50Hz or 60Hz in 60s
Plating	Silver/Gold
Plating Thickness	1.25um, 5um/ 3u", 6u", 15u", 30u", 50u"



Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Type		Product		Colour	
B/UTP UTP		VPI VDP Voice IDC Panel Voice Distribution Panel		BLK GRY Black BLK Grey SLV Black Silver	
▲		▲		▲	
B/UTP	C3	VPI	50P	BLK	
▼		▼			
Category 3	C3	25 Ports 150 Pairs 50 Ports	25P 150P 50P		
Category		Ports/Pairs			

Example Part Number	
Description	Part Number
BCP Unshielded Cat 3 50 Port Voice IDC Panel - Black	B/UTPC3VPI50PBLK