



Product Description

BCP® fibre optic distribution and termination boxes are used for the easy-access and distribution of fibre optic connections between networks.

Features & Benefits

- Suitable for mini-network terminal distribution
- IP54 Rating
- 96 FO
- Max 8 splice trays (12 FO per tray)
- RoHS compliant materials
- For use indoors

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- CATV - Cable television
- Fibre-to-the-Home (FTTH)

Technical Specifications

Material	Cold-rolled steel
Dimensions	380x450x129mm
Max Quantity of Splice Tray	8 pcs
Max Splice Tray Capacity	12 fibres
Max Capacity	96 fibres
IP Rating	IP54



Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Product (Box)		Material		Polish Type*		No of Fibres	
B/ITB	Indoor Terminal	P	Plastic	A	APC	01	1 Pieces
B/IDB	Indoor Distribution	M	Metal	U	UPC	02	2 Pieces
B/OTB	Outdoor Terminal					04	4 Pieces
B/ODB	Outdoor Distribution					06	6 Pieces
B/ISB	Indoor Splitter Box					08	8 Pieces
B/OSB	Outdoor Splitter Box					09	9 Pieces
B/DRB	DIN Rail Box						
⬆		⬆		⬆		⬆	
B/IDB	06	M	SC	U	SX	96	
	⬇		⬇		⬇		⬇
Model 1	01	SC	SC	Duplex	DX	Pigtails	/P
Model 2	02	E2000	E2	Quad	QD		
Model 3	03	MTP	MTP	Simplex	SX		
Model 4	04	FC	FC				
Model 5	05	ST	ST				
Model 6	06						
Model 7	07						
Model 8	08						
Model 9	09						
Model		Adapter Type		Capacity		Additional*	

*Leave column blank if unloaded.

Example Part Number	
Description	Part Number
BCP Indoor SC UPC SX 96 FO Splicing Distribution Box – Metal – Model 06	B/IDB06MSCUSX96