



Product Description

BCP® fibre optic distribution and termination boxes are used for the easy-access and distribution of fibre optic connections between networks.

Features & Benefits

- 36 FO
- Wall or pole mount
- SC, LC and FC adapters
- IP65 rating
- RoHS materials

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- CATV - Cable television
- Fibre-to-the-Home (FTTH)



Technical Specifications

Material	PC, ABS
Dimensions	250×200×72mm
Colour	Grey
IP Rated	IP65
Max Adapters	8 adapters
Max Core	36 fibres
End-Use Temperature	-40 +85°C
Insertion Loss	≤ 0.2db (1310nm & 1550nm)
Cable Diameter (mm)	Φ14
Cable Outlet Size (mm)	Φ2~5
PLC Splitter (PCS)	1/8*1



Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Product (Box)		Material		Polish Type*		No of Fibres	
B/ITB	Indoor Terminal	P	Plastic	A	APC	01	1 Pieces
B/IDB	Indoor Distribution	M	Metal	U	UPC	02	2 Pieces
B/OTB	Outdoor Terminal					04	4 Pieces
B/ODB	Outdoor Distribution					06	6 Pieces
B/ISB	Indoor Splitter Box					08	8 Pieces
B/OSB	Outdoor Splitter Box					09	9 Pieces
B/DRB	DIN Rail Box						
⬆		⬆		⬆		⬆	
B/ODB	03	P	LC	U	QD	36	
	⬇		⬇		⬇		⬇
Model 1	01	SC	SC	Duplex	DX	Pigtails	/P
Model 2	02	E2000	E2	Quad	QD		
Model 3	03	MTP	MTP	Simplex	SX		
Model 4	04	FC	FC				
Model 5	05	ST	ST				
Model 6	06						
Model 7	07						
Model 8	08						
Model 9	09						
Model		Adapter Type		Capacity		Additional	

*Leave column blank if unloaded.

Example Part Number	
Description	Part Number
BCP Outdoor LC UPC Quad 36 FO Outdoor Splicing Distribution Box – Plastic – Model 03	B/ODB03PLCUQD36