



Product Description

BCP® fibre optic distribution and termination boxes are used for the easy-access and distribution of fibre optic connections between networks.

Features & Benefits

- 96 FO (4 x 24 fibre tray)
- IP65 & IK10 Rated (harsh environment & temperatures)
- UV resistant
- RoHS materials
- For use outdoors

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- CATV - Cable television
- Fibre-to-the-Home (FTTH)

Technical Specifications

Dimensions	345×220×95mm
Material	ABS + PC
Cable Port	1 Express Port (mid span), 2 Cable Glands
Max Capacity	96 Cores 4 x 24 Fibre Tray
Max Reinforced SC Adapter Qty	16pcs Mini SC coupler
Max PLC Splitter	2 Pcs 1:8 or 1pc 1:16 Block-less Splitter
Net Weight	1.2kg
Colour	Grey, Black



Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Product (Box)		Material		Polish Type*		No of Fibres	
B/ITB	Indoor Terminal	P	Plastic	A	APC	01	1 Pieces
B/IDB	Indoor Distribution	M	Metal	U	UPC	02	2 Pieces
B/OTB	Outdoor Terminal					04	4 Pieces
B/ODB	Outdoor Distribution					06	6 Pieces
B/ISB	Indoor Splitter Box					08	8 Pieces
B/OSB	Outdoor Splitter Box					09	9 Pieces
B/DRB	DIN Rail Box						
⬆		⬆		⬆		⬆	
B/OSB	23	P	LC	A	DX	96	/P
⬇		⬇		⬇		⬇	
Model 1	01	SC	SC	Duplex	DX	Pigtails	/P
Model 2	02	E2000	E2	Quad	QD		
Model 3	03	MTP	MTP	Simplex	SX		
Model 4	04	FC	FC				
Model 5	05	ST	ST				
Model 6	06						
Model 7	07						
Model 8	08						
Model 9	09						
Model		Adapter Type		Capacity		Additional	

*Leave column blank if unloaded.

Example Part Number	
Description	Part Number
BCP Outdoor LC APC Duplex 96 FO Splitter Distribution Box with Pigtails – Plastic – Model 23	B/OSB23PLCADX96/P