



Product Description

BCP® fibre optic distribution and termination boxes are used for the easy-access and distribution of fibre optic connections between networks.

Features & Benefits

- 96 FO
- Max 4 splice trays (24 FO each)
- IP65 & IK10 Rated (harsh environment & temperatures)
- UV resistant
- RoHS materials
- For use outdoors

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- CATV - Cable television
- Fibre-to-the-Home (FTTH)

Technical Specifications

Dimensions	345×220×95mm
Material	ABS + PC
Cable Entry	1 Uncut Port: 10-16.5mm; 2 Reserved Cable Entrance: 8-16.5mm
Cable Output	16 Outputs for Drop Cable
Max. Capacity	96 Fibres, 4 Trays x 24F
Adapter	Max 24pcs SC Simplex
Sealing Structure	Mechanical Sealing
PLC Splitter	Max Micro 1x16 Splitter
Colour	Grey
Application	Wall mount; Pole mount
Weight	1.85kgs



Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Product (Box)		Material		Polish Type*		No of Fibres	
B/ITB	Indoor Terminal	P	Plastic	A	APC	01	1 Pieces
B/IDB	Indoor Distribution	M	Metal	U	UPC	02	2 Pieces
B/OTB	Outdoor Terminal					04	4 Pieces
B/ODB	Outdoor Distribution					06	6 Pieces
B/ISB	Indoor Splitter Box					08	8 Pieces
B/OSB	Outdoor Splitter Box					09	9 Pieces
B/DRB	DIN Rail Box						
⬆		⬆		⬆		⬆	
B/OSB	26	P	SC	A	SX	96	/P
⬇		⬇		⬇		⬇	
Model 1	01	SC	SC	Duplex	DX	Pigtails	/P
Model 2	02	E2000	E2	Quad	QD		
Model 3	03	MTP	MTP	Simplex	SX		
Model 4	04	FC	FC				
Model 5	05	ST	ST				
Model 6	06						
Model 7	07						
Model 8	08						
Model 9	09						
Model		Adapter Type		Capacity		Additional	

*Leave column blank if unloaded.

Example Part Number	
Description	Part Number
BCP Outdoor SC APC Simplex 96 FO Splitter Distribution Box with Pigtails – Plastic – Model 26	B/OSB26PSCASX96/P