



### Product Description

With an array of lengths, thicknesses and compartments BCP® PVC cable trunking is adaptable and suitable for a large variety of installations. These PVC cable duct fittings allow the moldings to be connected and facilitate installation

### Features & Benefits

- Flat angle, internal angle, external angle, end cap coupling, flat and T-angle
- Self-extinguishing PVC at 650°C
- IP43 rated
- Smooth surface
- Suitable to be buried in concrete
- Good insulation
- Able to resist 25 KV voltage
- Low friction and high flow capacity

### Applications

- Data centres
- Telecommunication networks
- LAN

### Technical Specifications

|                |                                                                                    |
|----------------|------------------------------------------------------------------------------------|
| Material       | PVC                                                                                |
| Colour         | White RAL 9016                                                                     |
| Type           | Flat angle<br>Internal angle<br>External angle<br>End cap coupling<br>Flat T angle |
| Outside Corner | 20 x 12<br>25 x 16<br>40 x 16<br>60 x 16<br>20 x 12<br>25 x 16                     |
| Inside Corner  | 40 x 16<br>60 x 16                                                                 |

|                |                                                                |  |
|----------------|----------------------------------------------------------------|--|
| Flat Angle     | 20 x 12<br>25 x 16<br>40 x 16<br>60 x 16                       |  |
| T Angle        | 20 x 12<br>25 x 16<br>40 x 16<br>60 x 16                       |  |
| Outer End      | 20 x 12<br>25 x 16<br>40 x 16<br>60 x 16                       |  |
| Outside Corner | 20 x 12<br>25 x 16<br>40 x 16<br>60 x 16<br>20 x 12<br>25 x 16 |  |