

### Product Description

These special cable organisers patch panels are exclusively designed by BCP. Model 01, 24 Ports, has a unique cable locking system that is attached, tool-free, to any of our empty patch panels to enable easy and secure cable management. The locking mechanism has 6 positions to suit cable diameter ranging from 5.1mm to 8.8mm. The bar comprises 24 slots set over two rows (12 on each), with each locking arm rotating 180° for easy access.

### Features & Benefits

- Exclusive BCP design
- Flat front plate
- 25-year warranty
- Labelled Ports
- ANSI/TIA-568-C.2 & ANSI/TIA-568.0-D
- 19" 1U
- Suitable for Cat 8 to Cat 5
- 24 ports and adjustable cable slots
- Suitable for 5.1-8.8mm cables



### Applications

- Data and server racking
- Data centres
- LAN installations

### Technical Specifications

| Patch Panel                              |                                                                                  | Cable Organiser Slots               |                                   |
|------------------------------------------|----------------------------------------------------------------------------------|-------------------------------------|-----------------------------------|
| Norms                                    | ISO/IEC 11801 3rd Ed., EN 50173-1, ANSI/TIA-568-C.2, ANSI/TIA-568.0-D            | Slot Quantity                       | 24 (2 rows of 12)                 |
| Housing Material                         | 1.5 mm SPCC cold rolled steel sheet, powder-coated                               | Locking Positions                   | 6 nodes                           |
| Material Standard                        | EN 10 130(1991), BS 1449, NFA 36/401, DIN 1623, UNI 5866, ASTM, SAE, NFA 36/401  | Cable Diameter                      | 5.1-8.8mm                         |
| Grounding                                | Central ground connection                                                        | Distance Between Each Slot          | 17.10mm                           |
| Operation Temperature                    | -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA-568-C.2, ANSI/TIA-568.0-D) |                                     |                                   |
| <b>Cable Organiser Bar</b>               |                                                                                  | Depth of Locking Arm                | 4.9mm                             |
| Width                                    | 19"                                                                              | Rotation                            | 180°                              |
| Depth of Rear Bar                        | 28mm                                                                             | Full Height of Slot                 | Largest: 16.6mm; Smallest: 12.2mm |
| Overall Height                           | 42mm                                                                             | Overall height of management system | 29mm                              |
| Overall Depth (from back of empty panel) | 94mm                                                                             | Lock Type                           | Quick release                     |





## Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

| Empty                  |                    | Product          |                                        | Colour           |                  | Model     |          |
|------------------------|--------------------|------------------|----------------------------------------|------------------|------------------|-----------|----------|
| <b>B/EM</b>            | Empty              | <b>SCP</b>       | Special Cable<br>Organiser Patch Panel | <b>BLK</b>       | Black            | <b>01</b> | Model 01 |
| ▲                      |                    | ▲                |                                        | ▲                |                  | ▲         |          |
| <b>B/EM</b>            | <b>UTP</b>         | <b>SCP</b>       | <b>24</b>                              | <b>BLK</b>       | <b>1U</b>        | <b>01</b> |          |
| ▼                      |                    | ▼                |                                        | ▼                |                  |           |          |
| UTP (UTP)<br>STP (STP) | <b>UTP<br/>STP</b> | 1-24<br>24<br>48 | <b>1-24<br/>24<br/>48</b>              | 1 Unit<br>2 Unit | <b>1U<br/>2U</b> |           |          |
| Construction           |                    | Port Density     |                                        | Unit             |                  |           |          |

| Example Part Number                                                                   |                     |
|---------------------------------------------------------------------------------------|---------------------|
| Description                                                                           | Part Number         |
| BCP 1U 19" 24 Ports Keystone Jack Flat Panel UTP with Special Cable Organiser - Black | B/EMUTPSCP24BLK1U01 |